

Firewall Appliance Power UTM Aluminum

		TCP	UDP	
		Banda	Banda	Jitter
NO VPN	Bridge	939,00 Mbps	784,00 Mbps	0,029 ms
	Nat	942,00 Mbps	784,00 Mbps	0,025 ms
Open VPN	AES128	135,24 Mbps	121,74 Mbps	0,024 ms
	AES256	116,16 Mbps	106,88 Mbps	0,031 ms
	Blowfish	153,79 Mbps	138,41 Mbps	0,029 ms
IPSec	AES128	109,54 Mbps	106,77 Mbps	0,039 ms
	AES256	103,72 Mbps	96,06 Mbps	0,035 ms
	Blowfish 128	105,99 Mbps	95,01 Mbps	0,039 ms
	3DES	62,82 Mbps	54,86 Mbps	0,024 ms

Jitter: In the context of computer networks, jitter is the variation in latency as measured in the variability over time of the packet latency across a network. A network with constant latency has no variation (or jitter).[3] Packet jitter is expressed as an average of the deviation from the network mean latency. However, for this use, the term is imprecise. The standards-based term is "packet delay variation" (PDV).[4] PDV is an important quality of service factor in assessment of network performance.

Deepen jitter: <http://en.wikipedia.org/wiki/Jitter>