

KERIO CONTROL SMALL UTM 3

		TCP	UDP	
		Banda	Banda	Jitter
NO VPN	Bridge	595,00 Mbps	653,00 Mbps	0,033 ms
	Nat	595,00 Mbps	535,00 Mbps	0,037 ms
Open VPN	AES128	62,77 Mbps	75,50 Mbps	0,038 ms
	AES256	56,10 Mbps	65,30 Mbps	0,064 ms
	Blowfish	71,93 Mbps	87,10 Mbps	0,040 ms
IPSec	AES128	60,13 Mbps	67,20 Mbps	0,042 ms
	AES256	56,03 Mbps	63,20 Mbps	0,049 ms
	Blowfish 128	56,87 Mbps	66,10 Mbps	0,057 ms
	3DES	34,43 Mbps	37,10 Mbps	0,042 ms

Jitter: In the context of computer networks, jitter is the variation in latency as measured in the variability over time of the packet latency across a network. A network with constant latency has no variation (or jitter).[3] Packet jitter is expressed as an average of the deviation from the network mean latency. However, for this use, the term is imprecise. The standards-based term is "packet delay variation" (PDV).[4] PDV is an important quality of service factor in assessment of network performance.

Deepen jitter: <http://en.wikipedia.org/wiki/Jitter>